

R1200GSW SERVICE

Mileage: _____

Date: _____

Task	6K Service	12K Service		Notes
Read Fault Memory	[]	[]	[]	
Engine Oil Change w/filter	[]	[]	[]	SAE 5W-40, API SL / JASO MA2 Drain 42 Nm, Filter 11 Nm, Bash Plate 8 Nm
Final Drive Oil Change		[]	[]	180 ml Castrol SAF-XO Spray guard: 8 Nm w/loctite Drain and Filler: 20 Nm
Check valve clearance		[]	[]	Valves: intake 0.10 ~ 0.17 mm exhaust 0.34 ~ 0.41 mm TDC Plug: 30 Nm Cylinder head cover: 10 Nm Camshaft bearing cap: 10 Nm Camshaft sprocket: 65 Nm Camshaft sensor trigger: 6 Nm Chain tensioner to cylinder: 30 Nm
Replace spark plugs		[]	[]	NGK LMAR8D-J, Spark Plug: 12 Nm
Replace air filter cartridge		[]	[]	
Clutch system inspection	[]	[]	[]	Lines and fluid level
Front brake pads and discs	[]	[]	[]	Pad min 1 mm, Disc min 4.0 mm
Rear brake pads and disc	[]	[]	[]	Pad min 1 mm, Disc min 4.5 mm
Flush front brakes (2 yr)	[]		[]	Brake caliper 38 Nm, Bleed screw 10 Nm
Flush rear brakes (2 yr)	[]		[]	Brake caliper 24 Nm, bleed screw 14 Nm
Brake system inspection	[]	[]	[]	Lines and fluid level
Check coolant level	[]	[]	[]	
Check side stand	[]	[]	[]	
Check center stand	[]	[]	[]	
Check tires	[]	[]	[]	Front 36, Rear 42
Check lights	[]	[]	[]	
Check engine start supression	[]	[]	[]	Clutch switch, side stand switch
Check battery	[]	[]	[]	
Update service due date	[]	[]	[]	
Clear Fault Memory	[]	[]	[]	
Test Ride	[]	[]	[]	
Update maintenance log	[]	[]	[]	

Front Axle: 30 Nm
 Front Axle pinch bolt: 19 Nm
 Crash bar M8: 25 Nm
 Crash bar M10: 40 Nm

Handlebar weights: 40 Nm
 Handlebar riser/clamps: 19 Nm, tighten front first.
 Fuel tank: 19 Nm
 Rear wheel: 60 Nm